

PRODUCT SAFETY DATA SHEET

ACCORDING TO 93/112/EC

TM3 MOULDING MORTAR

| | | | | |
|--|----------------------------|--|-------|--------------------|
| 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY | | HARDENER component 2 of 2 | | |
| PRODUCT NAME AND CODE: TM3 MOULDING MORTAR - 3420 | | EMERGENCY NUMBER (OFFICE HOURS) 01639 730481 | | |
| COMPANY-UNDERTAKING IDENTIFICATION - ROTAFIX HOUSE, ABERCRAF, SWANSEA, SA9 1UR. TEL: 01639 730481 FAX: 01639 730858 | | | | |
| 2. COMPOSITION/INFORMATION ON INGREDIENTS | | | | |
| Description: Cycloaliphatic amine | | | | |
| CAS NO. | Description | % | Index | R-phrases |
| Mannich base | | 65-70 | C | 34, 43 |
| 140-31-8 | N-aminoethylpiperazine | 5-10 | C | 21, 34, 43, 52, 53 |
| 1477-55-0 | Benzene-1, 3-Dimethanamine | 10-12 | C | 20/21, 35 |
| 100-51-6 | Benzyl Alcohol | 8-20 | Xn | 20/22 |
| 3. HAZARDS IDENTIFICATION | | | | |
| Harmful by inhalation (R20). Causes burns (R34). May cause sensitization by skin contact (R43). Signs and symptoms of exposure (possible longer term effects) Repeated and/or prolonged contact with the skin may cause allergic reaction/sensitization. Repeated and/or prolonged exposures may result in: adverse eye effects (such as conjunctivitis or corneal damage). Adverse skin effects (such as defatting, rash, irritation or corrosion). | | | | |
| 4. FIRST-AID MEASURES | | | | |
| INHALATION: Remove victim to ventilated area - seek medical attention. | | | | |
| SKIN: Rinse with copious amounts of water, seek medical attention . | | | | |
| EYES: Rinse opened eye with plenty of water for at least 15 minutes, seek medical advice. | | | | |
| INGESTION: Do not induce vomiting. Drink 3-4 glasses of milk or water. Seek medical advice. | | | | |
| 5. FIRE-FIGHTING MEASURES | | | | |
| EXTINGUISHANTS LARGE FIRE/SMALL FIRE: Water spray, Carbon Dioxide (CO ₂), Dry Chemical, Alcohol Foam. | | | | |
| SPECIAL EXPOSURE HAZARDS: May generate toxic, irritating or flammable combustion products - carbon monoxide gas and toxic nitrogen oxide gases. | | | | |
| 6. ACCIDENTAL RELEASE MEASURES: Evacuate all personnel upwind from the spill, avoid contamination of ground and surface waters, notify local health authorities and other appropriate agencies if such contamination should occur Methods for cleaning up: Sweep up carefully and shovel into a container for disposal, absorb residual material on vermiculite and scoop up for disposal. Clean-up personnel must be equipped with self contained breathing apparatus and butyl rubber protective clothing. | | | | |
| 7. HANDLING AND STORAGE | | | | |
| HANDLING: Avoid contact with skin or eyes. Handle in well ventilated work space. | | | | |
| STORAGE PRECAUTIONS: Keep away from oxidizers, heat or flames. Keep in cool, dry, ventilated storage and in closed containers. | | | | |
| 8. EXPOSURE CONTROLS/PERSONAL PROTECTION | | | | |
| RECOMMENDED PROTECTIVE CLOTHING: Safety goggles, overalls and rubber gloves. | | | | |
| GENERAL PROTECTION AND HYGIENIC MEASURES: Keep away from foodstuffs, beverages and food. Instantly remove any soiled and impregnated garments. Wash hands during breaks and at the end of work. Avoid contact with eyes and skin. | | | | |
| 9. PHYSICAL & CHEMICAL PROPERTIES: | | | | |
| PHYSICAL STATE: Putty like paste | | APPEARANCE: Orange or off white | | |
| DENSITY @ 20°C: 1.15 | | ODOUR: Ammoniacal | | |
| VAPOUR DENSITY (AIR = 1): | | pH: 11 | | |
| VAPOUR PRESSURE @ 25°C: < 1 | | VISCOSITY @ 25°C: Thixotropic | | |
| SOLUBLE IN WATER: Insoluble | | | | |
| 10. STABILITY AND REACTIVITY | | | | |
| Materials to avoid: Oxidizing agents (i.e. perchlorates, nitrates etc.) A reaction accompanied by large heat release occurs when the product is mixed with acids. Hazardous decomposition products: Carbon monoxide in a fire: Carbon Dioxide in a fire: Ammonia when heated; Nitrogen Oxides in a fire. Nitrogen oxide can react with water vapours to form corrosive nitric acid. | | | | |
| 11. TOXICOLOGICAL INFORMATION | | | | |
| PRIMARY IRRITANT EFFECT: | | | | |
| ON THE SKIN: Harmful in contact with skin, corrosive to skin, may act as a sensitizer. | | | | |
| ON THE EYE: Can cause eye irritation. | | | | |
| 12. ECOLOGICAL INFORMATION: | | | | |
| Hazardous for water. Should not be allowed to enter sewers and water courses. | | | | |
| 13. DISPOSAL CONSIDERATIONS | | | | |
| Do not allow into drains or water courses. Wastes including emptied containers, are controlled wastes and should be disposed of in accordance with Local and National regulations made under the Control of Pollution Act and the Environmental Protection Act. Using information provided in this data sheet, advice should be obtained from the Waste Regulation Authority whether the special waste regulations apply. | | | | |
| 14. TRANSPORT INFORMATION | | | | |
| ADR/RID SHIPPING DATA | | | | |
| Corrosive Liquid, N.O.S. (mannich base/benzyl alcohol mixture) | | UN-number: 1760 | | |
| 15. REGULATORY INFORMATION | | | | |
| EEC SYMBOL - CORROSIVE (C) | | | | |
| Designation according to EC guidelines: This product has been classified and labelled in accordance with EC directives See paragraphs 2, 3, and 8 | | | | |
| 16. OTHER | | | | |
| Customers are urged to ensure that the product is entirely suitable for their own purpose. It is the customer's responsibility to ensure that a suitable and sufficient assessment of the risks created by a work activity using this product is undertaken before this product is used. This information contained herein is based on our present knowledge however, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. | | | | |