

RESIWOOD® SYSTEM STAIN KIT



PRODUCT CODE: 3431

DESCRIPTION: The Stain Kit consists of 4 acrylic water based liquid stains. The system is designed for application to either prepared timber or **TM3 MOULDING MORTAR**.

PACKAGING: The Stain Kit tub contains 4 pots consisting of 4 shades of brown plus a pair disposable gloves and mixing sticks.

PREPARATION: Timber should be sanded and brushed clean prior to the application of the stain. To afford the best penetration, **TM3 MOULDING MORTAR** must be sanded after cure and prior to staining.

MIXING: All 4 stains are concentrated and should be diluted with clean water (please try a test sample out on separate piece of timber before applying the stain)

APPLICATION: The stain may be applied by brush or cotton swab, dilute according to the degree of staining required. All combinations of the stain can be used simultaneously in order to obtain variegations of colour or difference in shade.

The additional use of a wire brush on **TM3 MOULDING MORTAR** will help to simulate the grain of any adjacent timber. To increase the darkness of a stain, allow the first coat to dry before making a second application.

RESIWOOD stain is a stand alone coating system. It will also accept overcoating with other products such as flame retardent varnishes.

COVERAGE: Coverage is dependent upon timber species and density.

CURE SCHEDULE: Cure times are dependent upon temperature, relative humidity, timber species and density. The stain is normally sufficiently dry within 1 hour at +20°C and an R.H. not exceeding 40%.

CURED PROPERTIES: The system is suitable for exterior application.

SPECIFIC USES: Cosmetic treatment to timber and timber substitutes. Protection of timber. High performance timber protective coating

CLEANING OF TOOLS: Uncured stain may be readily removed with soap and water. Mechanical methods are required to remove cured material.

The requirements for a Rotafix product(s) may be specific for an individual project. Advice given by Rotafix can only be considered as part of the contract if it is provided in writing.

ROTAFIX aqueous based polymer materials do not normally present a hazard. However, the normal precautions when handling aqueous polymers include the use of gloves and protection to the face and eyes from splashes. In the event that splashing occurs, apply copious amounts of water.

The information in this document is based on practical tests, but given without guarantee insomuch as methods of use by others is beyond our control. Due to continuing development and improvements, it may be necessary to change without notice the material specification. All goods are sold subject to our Standard Conditions of Sale.

RESIWOOD is a Registered Trade Mark of Rotafix (Northern) Ltd

ROTAFIX, ROTAFIX HOUSE, ABERCRAF, SWANSEA SA9 1UR. U.K.

TEL: +44 (0)1639 730481

FAX: +44 (0)1639 730858

e.mail: sales@rotafix.co.uk

Website: www.rotafix.co.uk

SOUTHERN AREA CONTACT: TEL: +44 (0)1442 243169 FAX: +44 (0)1442 234901