

SPHERIGLASS

PRODUCT CODE: 3614

DESCRIPTION: A solid glass bead for use in skid resistant flooring systems, abrasives and relective coatings.

PACKAGING: Supplied in 500 gram screw cap plastic jars.

PREPARATION: Not applicable

MIXING: Not applicable

APPLICATION: Normally applied into last but one or final paint coat to aid in forming an skid resistant surface.
Applied by throwing small quantities into the air so it lands evenly not in clumps.

COVERAGE: 500 grams of spheriglass would normally cover 25m² of coated floor area

CURED PROPERTIES: Particle shape/size - round/250/450 microns
colour - white to clear
Hardness (mohs) - 6.0
Specific gravity - 2.46g/cm³
Bulk Density - 1.60g/cm³
Refractive Index - 1.52
Oil absorption - 17g/100g

SPECIFIC USES: Skid resistant flooring and reflective coatings

GENERAL INFORMATION: Irritating to eyes and respiratory system if exposed to high concentrations.

The information in this document is based on practical tests, but given without guarantee insomuch as methods of use by others is beyond our control. Due to continuing development and improvements, it may be necessary to change without notice the material specification. All goods are sold subject to our Standard Conditions of Sale.

ROTAFIX, ROTAFIX HOUSE, ABERCRAF, SWANSEA SA9 1UR. U.K.
TEL: +44 (0)1639 730481 FAX: +44 (0)1639 730858
e.mail: sales@rotafix.co.uk Website: www.rotafix.co.uk

SOUTHERN AREA CONTACT: TEL: +44 (0)1442 243169 FAX: +44 (0)1442 234901