



ALUMINIUM OXIDE

PRODUCT CODE:	3608
DESCRIPTION:	Aluminium oxide is a treated version of corundum, commonly known as emery. It originates from bauxite. It is just below silicon carbide and diamond on the hardness scale.
SPECIFIC USES:	As a skid resistant dressing for foot and particularly heavy duty vehicular traffic such as RO – RO ferry ramps and highway hazard areas.
PACKAGING:	Sold per kilogram. Also available in 25 kilogram non-returnable sacks.
PREPARATION OF SUBSTRATE:	Treat the substrate with the appropriate adhesive coating or screed and apply the aluminium oxide in accordance with the specification.
MIXING:	No mixing is required. Use dry and broadcast as required.
APPLICATION AND EQUIPMENT:	Normally by hand, distribution box, or, where large areas are required, special air blowing equipment.
CURE SCHEDULE:	Not applicable.
MATERIAL USAGE:	Depends on specification and grade size to be used, normally between 2 kilograms per square metre and broadcast to excess.
CURED PROPERTIES:	Hard, inert, sub-angular surface with a MOH hardness 9 (diamond is 10).
CLEANING OF TOOLS:	Not applicable.

The site conditions and equipment required when using individual Rotafix products are specific for each project. Only advice given by Rotafix in writing will be considered as part of our contractual liability.

The information in this document is based on practical tests. It is given without guarantee inasmuch as methods of use by others is beyond our control. Due to continuing development and improvements, it may be necessary to change without notice the material specification. All goods are sold subject to our Standard Conditions of Sale which are freely available from our offices.

ROTAFIX, ROTAFIX HOUSE, ABERCRAF, SWANSEA SA9 1UR. U.K.
TEL: +44 (0)1639 730481 FAX: +44 (0)1639 730858
e.mail: sales@rotafix.co.uk Website: www.rotafix.co.uk

SOUTHERN AREA CONTACT: TEL: +44 (0)1442 243169 FAX: +44 (0)1442 234901